



**IXOM Watercare Inc.**  
 3225 Hwy 22, Dickinson ND 58601  
 866-437-8076 • watercare@ixom.com

**Budget Estimate - ( Bid Specs Vary, Do Not Use for Bid Pricing )**  
**GS-12 / GS-9 Electric Potable Water Tank Mixers**  
 Last Updated: February 22, 2021 - Note: International Pricing Will Vary



**Performance guaranteed or your money back!** GS Mixers are the most effective and competitively priced mixers on the market with the lowest life cycle cost and the best warranty. Specifications can be found at [www.ixomwatercare.com/equipment/gs-series-submersible-mixers](http://www.ixomwatercare.com/equipment/gs-series-submersible-mixers)  
 Installing a GS mixer is well within the capabilities of most cities and contractors. GS mixers are usually installed directly under the hatch with no need to center it in tank. A GS Series Electric Mixer Training Video is available at: [www.ixomwatercare.com/video/1802/gs-11-minute-installation-training](http://www.ixomwatercare.com/video/1802/gs-11-minute-installation-training)

Description	GS-12	GS-9
GS Submersible Electric Mixer: with 75 ft of in-tank submersible electrical cable	<b>\$9,925</b>	<b>\$7,450</b>
GS Submersible Electric Mixer: with 150 ft of in-tank submersible electrical cable	<b>\$10,385</b>	<b>\$7,850</b>
Freight cost for each basic system:	<b>\$100</b>	<b>\$80</b>
Horsepower, Voltage, Phase: GS Mixers are available on request at the same price: 240vAC 1PH and 460vAC 3PH	0.50 hp, 120vAC, 1PH Other voltage / ph available	
Mixer length x diameter, inches: 12" or larger hatch size required, no need to enter or drain the tank	36" x 10"	24" x 10"
Weight: submersible mixer only	75 lbs	65 lbs
Maximum recommended tank volumes for moderate conditions: * The GS-12 is recommended for higher turnover rate, or ice issues, or areas with high heat.	8 MG (million gallons)	3 MG (million gallons)

**Options**

**Mix-Guard Replacement Program:** Covers beyond the warranty, it replaces the mixer for Acts of God, lightning, vandalism, power problems, handling damage or any other issue.  
**Annual Cost: While in 5 yr warranty: GS-12 \$500/GS-9 \$400 - When beyond the 5 yr warranty: GS-12 \$900/GS-9 \$750**

100217 Chemical injection interior hose: per 100 ft:	<b>\$250</b>
100321 Chemical injection hose penetration thru fitting: for steel tanks:	<b>\$460</b>
Chemical injection exterior hose kit: includes 50 ft SS braided hose & valve termination:	<b>\$725</b>
Additional - Chemical injection exterior hose: price per ft:	<b>\$7.20 per ft</b>

101846 Control Box (120v): UL listed, NEMA 4, 120vAC/1ph, with SCADA monitoring, HOA switch, indicator light, locking latch	<b>\$1,545</b> Shipped with mixer for electrical contractor installation
101847 Control Box (240v): UL listed, NEMA 4, 240vAC/1ph, with SCADA monitoring, HOA switch, indicator light, locking latch	<b>\$1,855</b> Shipped with mixer for electrical contractor installation
100264 Control Box (120v): UL listed, NEMA 4X, 120vAC/1ph, with timer but No SCADA, on/off switch, indicator light, locking latch	<b>\$825</b> Shipped with mixer for electrical contractor installation

Factory Delivery & Placement: Installing the above mixer is within the scope of work that most cities/contractors can perform	<b>\$14,000</b> Varies with tank height and tank construction
---	--

DBS - Portable Disinfectant Boost System: An electric or engine-driven air compressor (4 cfm @ 60 psi) is required to operate the air-powered diaphragm pump; air compressor is <u>not included</u>	<b>\$9,070</b> <b>+ \$450 Freight</b>	
--	--	--