CHLORINE CDU STORAGE & DOSING UNIT

Key Product Features:

- Storage capacity up to 2 x 920 kg drums or 70 kg cylinders
- Any ColorBond[™] colour
- Ixom's unique drum trolley system
- ChlorGuard[™] emergency shutdown system
- Portable with minimal site civils
- AS/NZS 2927 compliant
- Delivered fully assembled & ready to use.





Ixom has developed an innovative, safe and cost effective solution for the storage and dosing of Chlorine for small to medium applications.

The solution incorporates a portable building which allows the system to be fully designed, built and factory tested by Ixom thereby minimising the cost, risk and time associated with site installation works.

lxom's system complies with all legislative requirements and AS/NZS 2927.



What's your challenge?



For specialist advice in an emergency, call lxom's 24 HOUR EMERGENCY RESPONSE SERVICE

Ixom Water Treatment Systems 1 Nicholson St East Melbourne VIC 3002

Australia **T Australia** 1300 559 262

Australia +61 3 9906 3000 New Zealand

+64 9 368 2700 International +61 3 9663 2130

Important Notice

While the information contained here is lxom's best knowledge at the date of publication, lxom makes no representation about the accuracy of the information. If you need clarification or more information, you should contact lxom. Ixom's equipment and technology applications and solutions are designed to fit the specific requirements and conditions of each customer site operations. The outcomes of its equipment and technology applications may differ between operations and sites. To the extent legally permissible lxom accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of lxom's products or reliance upon the information contained here. Issued by lxom WTS, a division of lxom Operations Pty Ltd (ABN 51 600 546 512), 1 Nicholson Street, Melbourne. Ixom and the lxom logo are trademarks of lxom Group.



Product Guide Solving our customers' challenges



Safety In Design

Each Chlorine CDU has been designed to incorporate lxom's extensive knowledge and best practice in chlorine gas storage. Ixom's Chlorine CDUs meet the requirements for AS/NZS 2927 and have been developed using the Ixom HAZOP process to minimise operational and safety risks.

Configurable Product To Suit Your Application

- High pressure carrier water dosing
- Integrated inline water quality instruments
- Building insulation with air conditioning
- Combination of 70 kg and 920 kg duty or duty/ standby configurations
- Multiple carrier water dosing combinations
- Pressure pump system for eyewash showers

What's your challenge?

Ixom Water Treatment Systems

1 Nicholson St East Melbourne VIC 3002 Australia

T Australia 1300 559 262 New Zealand 0800 222 277 All other locations 61 3 9906 3000

E water.treatment@ixom.com

ixom.com

For specialist advice in an emergency, call lxom's 24 HOUR EMERGENCY RESPONSE SERVICE

Australia +61 3 9906 3000

+61 5 9906 5000 New Zealand +64 9 368 2700

International +61 3 9663 2130

Important Notice

While the information contained here is lxom's best knowledge at the date of publication, lxom makes no representation about the accuracy of the information. If you need clarification or more information, you should contact lxom. Ixom's equipment and technology applications and solutions are designed to fit the specific requirements and conditions of each customer site operations. The outcomes of its equipment and technology applications may differ between operations and sites. To the extent legally permissible lxom accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of lxom's products or reliance upon the information contained here. Issued by lxom WTS, a division of lxom Operations Pty Ltd (ABN 51 600 546 512), 1 Nicholson Street, Melbourne. Ixom and the lxom logo are trademarks of lxom Group.